

## Overview

Stainless steel nozzles with 4 front jets. Available upon request with carbide inserts.



## Characteristics

### APPLICATIONS

- penetration through occlusion of soap, grease, stones
- preliminary cleaning jobs before using chain rotating nozzle for roots removal
- reverse cleaning jobs (from house to main sewer)





### ADVANTAGES

- sharp chisel shape improves breaking performance

# Technical Specifications

<b>Inlet</b>	1/4" F	3/8" F	1/2" F	3/4" F	1" F
<b>Ø x L (mm)</b>	19 x 30	25 x 40	38 x 55	52 x 85	69 x 115
<b>Weight (kg)</b>	26 gr	80 gr	240 gr	690 gr	1,57 kg
<b>Front Inserts</b>	-	3 x 15° + 1 M4	3 x 15° + 1 M6 C	3 x 20° + 1 TE M6 C	3 x 20° + 1 TE M6 C
<b>Rear Inserts</b>	-	6 x 20° drilled	6 x 20° M6 C	6 x 20° TE M6 C	6 x 20° TE M6 C
<b>Maximum Pressure (bar)</b>	300	300	300	300	300
<b>Flow (lt/min)</b>	35-80	35-90	70-170	85-240	100-350
<b>Working DN (mm)</b>	30-100	30-100	50-250	80-300	150-400

## Items

	<b>Part Number</b>	<b>Description</b>
	5550.05	1/4" F RAUT NOZZLE
	5560.08	3/8" F RAUT NOZZLE SS DRILLED
	5560.10	1/2" F RAUT NOZZLE SS with ceramic inserts
	5560.20	3/4" F RAUT NOZZLE SS with ceramic inserts



5560.30

1" F RAUT NOZZLE SS with ceramic inserts

---

## GALLERY IMAGES

