

Low pressure sanitizing agent sprayer

Pressure from 2 to 8 Bar

Microspray

17.1



TECHNICAL DETAILS

Microspray is a small high performance sanitizing agent sprayer .

Its stainless steel lance generates a special mist, making it ideal for disinfecting vertical surfaces and ceilings, with low consumption of sanitizing agent .

- ✓ Water flow : 250 l/h (mean value)
- ✓ Water: From 2 to 8 bars (normally mains pressure is between 2 and 4 bars)
- ✓ Working temperature : 50°C Max
- ✓ Surface treated : About 25 m2 per minute
- ✓ Dimensions: 100x155x50 mm (L x H x P)
- ✓ Weight: 6 kg
- ✓ Material box: Stainless steel AISI/304
- ✓ Venturi system: Stainless steel AISI/316
- ✓ Product aspirated : from 0,1 % to 5 %

Whelled version:

- ✓ Stainless steel trolley
- ✓ S/s Pivoting front wheels \varnothing 100 with brake
- ✓ Rear Wheels \varnothing 100 mm

Microspray

17.1



Ø Foro inc Ø Size inc	Ø Foro mm Ø Size mm	Img	Colore Color
No Hole	Non forato		Trasparente Clear
0,01	0,25400		Rosa Pink
0,014	0,35560		Porpora Purple
0,018	0,45720		Azzurro Aqua
0,02	0,50800		Giallo Yellow
0,023	0,58420		Marrone Brown
0,025	0,63500		Arancione Orange
0,028	0,71120		Verde Green
0,035	0,88900		Bronzo Tan
0,04	1,01600		Blu Blue
0,043	1,09220		Bianco White
0,052	1,32080		Rosso Red

STANDARD ACCESSORIES

- ✓ Stainless steel spray lance 600 mm complete of special nozzle
- ✓ Pvc gun resistant to impact and corrosion
- ✓ Antispot hose L= 20 mt
- ✓ N. 01 detergent suction hose L= 1,5 mt with filter
- ✓ Full screen printing illustration of the dosage in percentage
- ✓ Stainless steel hose holder
- ✓ Dosage regulator in Stainless steel with microperforated colorful inserts
- ✓ Microperforated colorful inserts kit to determinate the percentage of product aspirated

AVAILABLE CONFIGURATION

CODE	WATER FLOW RATE (lt/h)	PRESSURE (Bar)	PERCENTAGE OF ASPIRED PRODUCT (%)	WEIGHT (Kg)	DIMENSIONS LxHxP (mm)	MAX TEMPERATURE IN-LET
15755	~250	2 ~ 8	0,1 ~ 5	6	100x155x50	50 °C

AVAILABLE CONFIGURATION OF THE WHEELED VESRION

CODE	FOAM DISPENSER STATION	FLOW RATE (lt/h)	WATER PRESSURE (Bar)	WATER IN-LET MAX TEMPERATURE	PERCENTAGE OF ASPIRED PRODUCT (%)	WEIGHT (Kg)	DIMENSIONS LxHxD (mm)
30650	MICROSPRAY	~250	2 ~ 8	50 °C	0,1 ~ 5	25	580x1070x750